

# PCP Shrouds

## Polychloroprene Shrouds

ROHS COMPLIANT

### Specifications

Design No.	Length A	Length B	Ø C	Ø D max	Ø E min	Gland Fit	
						A1/A2	CW / E type
401AA-02	73	56	11	25	22.5	20ss/20s/20	16/20ss/20s
401AA-03	75	57	12.4	29.5	27	25	20
401AA-05	81	61	16	41.5	36	32	25
401AA-06	93	67	22.5	46.5	41	40	32
401AA-07	98	71	28	59	53.5	50s / 50	40
401AA-09	104	76	38.5	67.5	62.5	63s	50s / 50
401AA-11	106	79	49.5	81	75.5	63 / 75s / 75	63s / 63
401AA-13	119	89	60.5	101	94	90	75s / 75
401AA-14	130	95	72	111	107		
401AA-22	85	70	7.7	29.5	27		20s Barrier
401AA-30	73	56	11	25	22.5		
401AA-31	81	61	16	41.5	36		

# LSOH Shrouds

## Silicone LSOH Shrouds

COMPLY WITH LU STANDARD 1-085 FOR INSTALLATION IN ALL SUB-SURFACE LOCATIONS

### Specifications

Design No.	Length A	Length B	Ø C	Ø D max	Ø E min	Gland Fit		
						BW	A1/A2	CW / E type
401LSF-02	73	56	11	25	22.5	20s	20ss/20s/20	16/20ss/20s
401LSF-03	75	57	12.4	29.5	27	20	25	20
401LSF-05	81	61	16	41.5	36	25	32	25
401LSF-06	93	67	22.5	46.5	41	32	40	32
401LSF-07	98	71	28	59	53.5	40	50s / 50	40
401LSF-09	104	76	38.5	67.5	62.5	50	63s	50s / 50
401LSF-11	106	79	49.5	81	75.5	63	63 / 75s / 75	63s / 63
401LSF-13	119	89	60.5	101	94	75s / 75		75s / 75

